VIDEO MONITORING AND CONFERENCING SYSTEM

Reference to Related Applications

This application is a continuation-in-part of co-pending U.S. Serial Nos. 08/050,861, filed April 21, 1993, now U.S. Pat. No. 5,450,140 and 08/298,104, filed August 30, 1994. now U.S. Pat. No. 5,537,157

Field of the Invention

5   This invention relates generally to video monitoring, and, more particularly, to such systems employing means for digitizing camera images for display at a first image size, sampling rate, and frame rate, and for
10   digital storage at a second image size, sampling rate, and frame rate.

Background of the Invention

Existing systems for monitoring video signals from multiple sources either have relied upon switching
15   means to sequence through each of the sources in a predetermined pattern, or else implement some form of "split screen" display, in which a conventional video monitor displays, for example, the output of four cameras, each occupying a portion of the display screen. Often, the
20   video output is also supplied to signal storage means such as a VCR which is operated in a single-frame recording mode, providing a time-lapse record of the camera outputs. These types of systems are in common usage, and are well known in the art.

25   More recently, the availability of digital techniques for video signal processing and data compression

1

2

has opened new video monitoring alternatives. Mathisen, for example, U.S. Pat. No. 4,198,656, describes a system employing a signal selector which is controlled by signal storage means, including a VCR functioning as a time-lapse

5   frame recorder, and disc storage means functioning as a frame-store type device which provides continuity in the display while the selector is advancing through its sequence to the next signal source, or to the next recorded signal from one particular source. Each image is further

10   provided with a digital code, which enables the image source to be identified upon playback.

Katz (U.S. Pat. No. 5,216,502) discloses a system for monitoring and recording transactions at multiple cashier lanes. According to the preferred embodiment,

15   output signals from four cameras are fed to a four-quadrant multiplexer, which contains a frame store having provisions for reducing each camera image to one-quarter size and then displaying it in one of the four quadrants of the video monitor. The combined output signal is then recorded on a

20   Video Cassette Recorder (VCR) to provide a more permanent record of the transaction. No description is given of the size-reduction method, but this kind of display may be implemented by employing a time-compression scheme for the horizontal lines, and eliminating alternate scan lines from

25   the vertical dimension of the video frame. Data from the individual cash registers is encoded digitally, and then either recorded on lines of video in the vertical-interval or else recorded on the audio tracks of the VCR. The monitoring provisions include a video overlay generator, so

30   that transaction information may be displayed concurrently

2

with images of the event. Provisions are also included for selective recording of representative frames of video, as triggered by transaction events at individual cashier lanes. This further reduces the number of frames recorded,

5   and extends the recording duration of the video cassette.

Neither of these two inventions disclose the use of image data compression schemes, nor of image resizing by digital means. Katz does disclose selective recording of frames of video, but only in analog form, and using

10   conventional video recording means, such as a VCR.

Blum et al. (U.S. Pat. No. 5,237,408) disclose a system employing multiple interface circuit boards containing provisions for capturing and digitizing images from a plurality of cameras, further storing a slow-scan

15   sequence of images for each camera in active buffer memory means as RAM on each of the interface boards. The display of these image sequences is preferably controlled by a PC with disk storage capabilities, and individual images selectively may be recorded on the hard disk, under

20   operator control. Storage capacity is limited, however, because no image data compression is provided, and it is not practical to store large quantities or sequences of images. There are no provisions for automatic recording of images, nor any provision for storing these images in a

25   data form differing from the display format image size.

Gormley (U.S. Pat. No. 5,258,837) discloses video compression means as a method for fitting multiple camera images within a single video display screen. However, Gormley clearly indicates that the system relies on fixed

30   image-size compression of the digitized incoming video

3

signal, and does not perform any kind of bandwidth compression. Provisions are included for storing images on a video recorder, but, as in other systems, these images are stored by taking the screen display as a whole, rather

5   than storing independently constituted representations of the individual camera outputs.

In general, these conventional systems, regardless of the subsequent signal processing employed, accept analog video signals from the camera sources for

10   input to the monitoring system. As such, these signals are susceptible to disturbances such as RF interference, ground-loop noise, and high-frequency signal loss due to long runs of coaxial cables. Automatic video switcher units sequence the source signals at a relatively slow

15   rate, requiring as much as 16 seconds delay between successive viewings of a particular source when using a one source-per-second rate to sequence through 16 sources. When such a system is equipped with a time-lapse video recorder, the recording medium is expensive, has low

20   resolution, and is limited in recording capacity.

Other systems, such as video conferencing arrangements, use multiple camera images and audio sources which are coordinated through electronic switching means and image display means, with interconnections between

25   conferencing rooms locally or at remote sites via telephone lines or other communications links. Fabris et al. (U.S. Pat. No. 4,516,156) discloses a sophisticated implementation of such a system, employing satellite links for long-distance communications, a full range of camera

30   remote controls (including lens controls and pan-tilt-head

4

controls), and touch-screen monitor facilities for system controls of cameras and signal switching. This system, however, has no provisions for image storage, or any application of image data compression means coupled with
5   display means or image storage means.

Summary of the Invention

The present invention implements an automated video monitoring system by way of a PC-based platform employing display windowing software, with camera sources
10   being interfaced to an input circuit board which includes provisions for image data compression. Using a basic image size in pixels of 320 x 240, and optionally including color processing employing a Y-U-V 4:1:1 or 4:2:2 sampling technique, a range of performance standards are
15   established. An economical simultaneous display of 4 sources in a 2 x 2 configuration on a conventional 10" VGA-format (640 x 480 pixels) monitor may be upgraded to a more elaborate 24-source (plus one utility window, which also may be used as a graphical-based input source device
20   for transmitting control commands to the individual cameras) display in a 5 x 5 configuration on a high-resolution 20" (1600 x 1200 pixels) monitor. Other combinations are possible, including arrays of images of size 640 x 480 pixels or even 800 x 600 pixels, depending
25   on the screen size of the display monitor and the capabilities of the video display adapter circuit card. In addition, not all image windows need to be of the same size, nor updated at the same rate, but rather they may be mixed and combined based on particular applications.

Remote controls for the individual cameras may be implemented by way of windowing software and/or monitor touch-screen devices. Automatic sensing of particular events (representing security alarms, equipment or process

5 disturbances, or a change in the person speaking in a videoconferencing environment) may be employed to cause reconfiguration by way of resizing the image or modifying the update rate of individual windows on the display screen, or by modifying the data format of recording images

10 on a storage device.

Storage of images may be implemented by way of a tape back-up device, such as a DAT or 8-mm tape recorder, which are capable of storing as much as 960 hours of monitoring images, or by way of disk storage devices,

15 preferably including removable disk drives such as magneto-optical disks or PCMCIA-compatible disk-drive modules. Images are preferably stored as a succession of data-compressed representations, corresponding to various window sizes sampled at diverse update rates; however,

20 though the image representations need not be identical to the sizes and rates used for video monitors displaying the various images. In an alternative embodiment, cameras are provided with data compression means at the camera location, with a bi-directional data link providing control

25 signals from the PC, and accepting data-compressed images from the cameras. Depending on the data rates selected, the transmission of these signals may be by means of coaxial cables, twisted-pair lines, or fiber-optic cables. These signals may alternatively be transmitted over

30 internal PBX telephone lines, or over greater distances,

6

including satellite links, as would be the case for remote monitoring of facilities or videoconferencing. The use of digital images allows the application of various useful techniques, such as digital noise reduction and

5 motion-sensing, to trigger security alarms, for example.

It is an object of the invention to provide a more efficient method for monitoring camera outputs by means of a multiple-window display system implemented on a computer platform.

10 It is another object of the invention to provide an improved recording system for event-logging or security applications, by means of storing data-compressed digital images, including identifying information, which are more representative of events than typical analog time-lapse

15 recordings, and further to implement this system on a computer platform.

It is a further object of the invention to provide extended recording time for event-logging or security applications by means of either tape-based, or

20 disk-based, or both tape-based and disk-based data recording means.

It is yet another object of the invention to provide a system for remote monitoring of cameras by means of transmission of data-compressed digital images over

25 communication links.

It is yet a further object of the invention to provide a convenient method of implementing videoconferencing facilities by means of a PC-based platform.

Brief Description of the Drawings

FIGURES 1-6 show various possible screen display configurations according to the invention;

FIGURE 7 is a functional diagram of a PC-based system wherein plug-in printed-circuit boards implement digital processing for analog input signals;

FIGURE 8 is a functional diagram of a plug-in printed-circuit board introduced with reference to Figure 7;

FIGURE 9 is a functional diagram of a universal camera adapter having digital output signals;

FIGURE 10 is a diagram of an integrated camera system;

FIGURE 11 is a functional diagram of a PC-based monitoring system adapted for videoconferencing at multiple remote locations;

FIGURE 12 is an overhead view of a physical layout of the system of Figure 11;

FIGURES 13A and 13B are drawings of a multiple-camera monitoring unit for table-top use in videoconferencing;

FIGURE 14 is a side-view of an expanded multiple-camera monitoring unit implemented for videoconferencing;

FIGURE 15 is a table listing a variety of possible operating modes, depending on computer monitor display facilities, in either a monitoring or a videoconferencing version of the invention.

Detailed Description of the Preferred Embodiment

The present invention implements an automated

8

video monitoring system by way of a PC-based platform employing display windowing software, with camera sources being interfaced to an input circuit board which includes provisions for image data compression. The basic video

5   window size of 320 x 240 pixels from each camera source can be displayed on a variety of video monitors, in a number of formats, depending on system complexity. The preferred recording medium is a 4-mm helical-scan data cartridge, commonly referred to as a digital audio tape (DAT). Each

10   tape cartridge is capable of storing 10 GB (gigabytes) of data. All recording times in the explanation below are based a data-compression ratio of 100:1, utilizing a 4:2:2 Y/U/V sampling method for color images. Other higher capacity media, such as 8-mm tapes capable of 20 GB of data

15   storage, may be employed when longer times are desired.

Figure 15 shows a variety of possible operating modes, depending on the particular implementation of the PC-based monitoring system. These six representative modes will be explained in detail with the understanding that the

20   invention is by no means limited to the specific examples shown, and that many different alternatives are possible. It should be noted also that in certain of the implementations shown, the entire screen may not be occupied by the various windows, and any unused areas at

25   the top, bottom, or sides may be utilized to display warning messages, control buttons, or other such facilities.

Figure 1 shows a computer monitor display for a system configured in accordance with Mode I as listed in

30   Figure 15. Using a commonly available 14" VGA-format

9

computer monitor with a dimension in pixels of 640 x 480, four windows having a dimension in pixels of 320 x 240 may be displayed simultaneously. Recording this data at the rate of one frame per second (1 fps) in black and white

5   (B/W) and with 100:1 data-compression on a 10 GB DAT tape provides approximately 960 hours of images per tape, or alternatively more than 480 hours of color images. A second monitor optionally may be used to display utility windows including various system operating controls, as,

10   for example, camera pan, tilt, zoom, focus, and so forth.

Figure 2 shows a computer monitor display for a system configured in accordance with Mode II as listed in Figure 15. Using a 15" to 17" SVGA-format computer monitor with a dimension in pixels of 1024 x 768, nine windows,

15   each having a dimension in pixels of 320 x 240, may be displayed simultaneously. Eight windows may be implemented as camera displays, and the ninth window may be used for the continuous display of the utility window, as described above. Recording of all eight windows at 1 fps will allow

20   480 hours of B/W images in this configuration per 10 GB DAT tape, or alternatively more than 240 hours of color images.

Figure 3 shows a computer monitor display for a system configured in accordance with Mode III as listed in Figure 15. Using a 17" to 20" high-resolution computer

25   monitor with a dimension in pixels of 1240 x 1024, eight windows having a dimension in pixels of 320 x 240 may be displayed, in addition to two windows having a dimension in pixels of 640 x 480. One of these larger windows may be implemented as a utility window, and the other larger

30   window may be implemented for sequential display of the

10

eight camera inputs at full camera resolution having a dimension in pixels of 640 x 480. Recording all eight camera image windows, and also the input-scan window, at 1 fps will allow 360 hours of B/W images in this

5   configuration per 10 GB DAT tape, or alternatively more than 180 hours of images in color.

Figure 4 shows a computer monitor display for a system configured in accordance with Mode IV as listed in Figure 15. Using a 20" high-resolution computer monitor

10   with a dimension in pixels of 1600 x 1200, 25 windows with a dimension in pixels of 320 x 240 may be displayed simultaneously. Twenty-four windows may be implemented as camera displays, and one is implemented as a the utility window. Recording all twenty-four windows, and also the

15   utility window, at 1 fps will allow 180 hours of B/W images in this configuration per 10 GB DAT tape. If color recording is desired, a 20 GB 8-mm data cartridge will allow 180 hours of color images.

Figure 5 shows a computer monitor display for a

20   system configured in accordance with Mode V as listed in Figure 15. Using a 20" high-resolution computer monitor with a dimension in pixels of 1600 x 1200, twelve larger windows having a dimension in pixels of 400 x 300 may be displayed, as well as one large high-resolution window,

25   with a dimension in pixels of 800 x 600, to display the sequentially scanned output of the camera images. Recording in this format at 1 fps will provide 180 hours of B/W images in this configuration per 10 GB DAT tape. If color recording is desired, a 20 GB 8-mm data cartridge

30   will allow 180 hours of color images.

Figure 6 shows a computer monitor display for a system configured in accordance with Mode VI as listed in Figure 15.   Using a 14" to 17" SVGA computer monitor with a dimension in pixels of 1240 x 1024, and implementing a

5   smaller window size with a dimension in pixels of 240 x 180, eight windows are available for the camera image displays, and two large windows of 480 x 360 are available for sequentially-scanned camera images.   Recording in this screen format at 1 fps allows 480 hours of B/W images in

10   this configuration on a 20 GB 8-mm data cartridge, and allows 240 hours of images in color.

In any of the display configurations just described, it is also possible to use a video overlay technique to display the utility controls superimposed on

15   the camera video.   Regardless of which display or recording format is used, the PC based monitoring system includes various facilities and features, which will now be described in further detail.

In operation, the user need only observe the

20   various display windows on the monitor screen, rather than concentrate on many monitors simultaneously, thereby reducing the risk of missing an important event.   Since no video switcher is used in recording, and images from all sources are continuously recorded at the selected frame

25   rate for each source, more information is recorded than in conventional analog systems, wherein events may be missed due to the sequential switching of input images.   The digital format also improves the picture quality, as the signal-to-noise ratio will be higher than for analog

30   systems.   In addition, there is no loss of quality during

12

recording or playback, and because the recording technique is digital, other types of information optionally may recorded along with the camera data, such as audio, time, date, location, etc.

5   An additional feature is the capability to implement a dual-recording-media option. This facility provides the ability to record simultaneously both on a tape (for high capacity, long term storage) and also on a removable media, such as a removable hard disk (i.e.

10   PCMCIA) or magneto-optical disk (for short-term storage of up to 24 hours of images). These disks facilitate high-speed searching of recorded information without interrupting the tape, as well as providing a back up for the recording on the tape. In addition, the system is

15   capable of simultaneously searching the recorded images on the disk storage unit while continuing to store images on the tape storage unit.

It should be noted that there is no requirement that the image sizes or frame rates utilized for the video

20   display match those utilized for the storage media. In practice, these two specifications may not agree, and will be determined by other factors, such as operator manipulation of the displayed image sizes or changes resulting from the detection of alarm conditions.

25   Figure 7 shows a functional diagram of an analog input-digital processing card installed in the PC which allows the use of existing analog cameras and cables with the PC-based monitoring system. This card, which may be obtained from such manufacturers as Nova, Model No. V-SW,

30   features four video inputs 2a-2d having balanced or

13

differential input circuitry for good noise immunity (or optically-coupled inputs for fiber-optic cabling), four video amplifiers 4a-4d, a 4x1 video switcher 6 by which any one of the four video inputs may be selected as a signal

5   source, and an analog-to-digital (A/D) converter 8. The recording of camera inputs is digital, however, there is no provision for remote control of camera functions such as pan, tilt, zoom, and so forth. If additional inputs are desired, multiple cards may be installed in the PC. The

10   output of the A/D converter 8 is supplied to the graphics processor and image data-compression engine 10. This unit performs the various functions required to configure the image sizes and frame rates as specified by the equipment operator. Because the overall data recording bandwidth of

15   the system is a factor in the selection of the individual picture data rates, computer software is provided to implement menu-driven management of the data bandwidth allocation to the various image sources. Based on this configuration, signals are provided to the video switcher

20   4 to facilitate the selection of the particular image sources as required. The data-compressed images are provided in digital form to the microprocessor data bus 12. The microprocessor unit (not shown) in turn provides control signals to the graphics processor 10 by way of this

25   data bus, in accordance with the image data allocation configuration selected.

        Figure 8 is a functional diagram of a digital input/output-digital processing card which implements bi-directional digital communications to and from the camera/

30   adapter unit over a single transmission line, thereby

14

greatly reducing the cost of cable and installation, and allowing existing wiring to be used. Various implementations of this printed-circuit card are required, depending on the type of network interconnection media

5   selected. In addition, system performance will depend on the type of network interconnection media. As an example, a fiber optic network will have a higher transmission rate and better signal quality than a telephone network. Interfacing technology for these communication methods are

10   in common usage and well known in the art. This printed-circuit card also serves four cameras through inputs 52a-52d, and additional cards can be implemented if required. The bi-directional digital video and camera control data switcher 54 serves to select the individual

15   image sources as explained in reference to Figure 7. These source signals are then provided to the graphics processor and image data-compression engine 56, which provides similar functions to those provided by the graphics processor 10, discussed in reference to Figure 7. The

20   processed data-compressed images are then provided to the microprocessor data bus 60. However, in this implementation, the bi-directional nature of the data switcher 54 is exploited to provide full functional control of the camera facilities through the bi-directional

25   controller 58. These functional controls include the cameras themselves (lens and exposure control) and the camera's physical mounting provisions (pan and tilt). The various control signals for these functions are those traditionally provided to these kinds of equipment, and

30   these concepts are well known in the art. In an

15

alternative embodiment, the individual cameras are each
equipped with separate image data-compression facilities,
utilizing such techniques as motion-JPEG or MPEG
compression.   In this case, control signals for these
5   additional functions are provided from the microprocessor
bus 60 through the bi-directional controller 58 and the
data switcher 54.

Figure 9 is a functional diagram of a digital
output universal camera adapter. This is a fully digital
10   version of the camera adapter as described in co-pending
U.S. Patent Application Serial No. 08/050,861, titled *now U.S. Patent No. 5,450,140*
"PERSONAL-COMPUTER BASED VIDEO PRODUCTION SYSTEM".   The
A/D-converter, digital image data-compressor, and bi-
directional interface camera adapter 100 accepts analog
15   audio and video signals from the camera 102, and converts
them to digital signals in anticipation of the transmission
of these signals over the interconnection network 104. The
camera adapter also receives camera control commands from
the PC by means of the interconnection network, and
20   translates them into the appropriate pan, tilt, zoom, focus
and iris control signals for the particular camera
equipment, including the camera lens 106 and the pan/tilt
mounting facilities 108. In addition, the camera adapter
also has inputs for several "alarm system" type sensors
25   110, as, for example, motion detectors, photocell
detectors, or simple switches. These alarm signals are
digitized, encoded, and then transmitted to the main PC by
means of the interconnection network. Power is supplied
for this equipment from a local source 112. This camera
30   adapter is implemented to provide a full-function system,

16

adaptable to all existing types of cameras and control equipment. However, because of the large number of interconnections involved in the adapter, camera, pan/tilt unit, and sensors, the installation process may be somewhat

5   complicated.

By equipping an individual camera input with digital frame store capabilities, it is possible to detect an alarm condition based on deviations from the normal-state image scene. For example, if a camera is

10   monitoring a door exit or an area of a warehouse aisle that is not utilized during evening hours, any change in the image would represent an alarm condition. To allow camera movement, this sensing process would be disabled during pan, scan, tilt, zoom, and other camera positioning

15   controls, and the sensing would be re-enabled after camera positioning ceased, or by manual operator control.

Figure 10 is a functional diagram of an integrated camera system according to the invention including means to overcome problems associated with having

20   a physically separate camera, pan/tilt unit, and adapter unit. The integrated system includes a camera 150 with pan/tilt control, A/D converter, digital data-compression circuitry, and requisite interfacing circuitry. Such provisions are preferably included in the camera base

25   structure 152, which simplifies installation, as no separate interconnecting cables are required. The integrated camera system optionally may include provisions for supplying electrical operating power from a network coaxial cable, and thereby may be implemented with only a

30   single interconnecting cable. An integrated camera system

17

of this type may be implemented in a physical package which is as small as the camera itself, since most of the electronics may be highly miniaturized by developing custom integrated circuits, including LSI, ASIC, DSP, and mixed-

5   signal processing.

It will be appreciated that in any of these implementations, alarm or sensor signals may be utilized to automatically re-configure the system operating mode, as, for example, increasing the frame rate or image size for an

10   image source associated with the sensor which has initiated the alarm signal condition. As explained above, the displayed windows and image sizes may be reconfigured into an operating mode different from the reconfiguration of the digital storage mode. If desired, the operator may choose

15   to allow the system to automatically adjust the compression ratio utilized for a particular window in response to alarm signal conditions. Alternatively, the compression ratio may be adjusted in response to the selection by the operator of a particular window for closer monitoring, by

20   switching to an image window having larger dimensions in pixels. For some applications, the use of a resolution-independent data compression scheme, such as the "Fractal Compression" method of Iterated Systems, Inc., will be preferred, since images compressed by this method may be

25   resized to fit larger or smaller windows as desired, without loss of apparent resolution. In addition, automatic switching of the audio signals associated with a particular window in response to alarm signal condition will enable the operator to fully investigate such events,

30   and the audio signals may serve to attract the operator's

18

attention to the event. Such switching optionally may be coupled with operator selections for monitoring purposes as well, and in both of these options may be integrated into the system previously described for recording the images,

5   with or without any associated audio signals, onto the mass-storage media.

        Figure 11 illustrates a PC-based monitoring system implemented for videoconferencing at multiple remote locations. In this application of the invention, a main

10   control center, shown generally as 200, is interconnected, by way of a network, with remote locations, shown generally as 204 to 210, designated as "1" through "N". The network 202 may be implemented by way of telephone lines (slow speed), ISDN lines (medium speed), or alternatively

15   coaxial cable or fiber optics cables (high speed). The higher speed implementations permit transmission at higher frame rates and higher image resolutions. As an alternative, wireless networks or microwave links optionally may be used. Network communication between the

20   main and remote locations is bi-directional; the main computer receives audio, video, and sensor data from each of the remote locations, and transmits controls for camera pan, tilt, focus, zoom, and so forth. Audio and video communications for the system operators also is provided,

25   by means of an additional camera and headset at each location.

        The application of these PC-based monitoring techniques also may he implemented in cases in which the central monitoring area may be located at some distance

30   from the remote site. In this case, the physical hardware

and networking facilities will follow the example shown in Figure 11, with the understanding that "Location 1" through "Location IN"' will now refer to separate monitoring for security applications or other monitoring purposes.

5   The purpose of the main control center is to manage multiple cameras at multiple locations.   By monitoring and controlling the remote locations from a central location 220, the system may function without an operator at each location.   Optionally, additional

10   computers shown, by way of example, as 222 and 224 at the main location may be implemented to simplify the monitoring and control of the remote locations.   The main control center stores the data from remote locations in the main control storage facilities, shown, by way of example, as

15   238, 240 and 242, using digital tape and removable media, including, by way of example, PCMCIA-based removable media or magneto-optical (MO) media.   The images may be stored at various frame rates and resolutions, depending on the requirements for the intended use of the stored images.

20   Intercom provisions as shown as 230, 232 and 234, facilitate the coordination of activities between the main control center and the various remote locations, and video camera units are provided at each of the computers, shown, by way of example, as 244, 246 and 248.

25   Each remote location includes a PC/monitor 250, with multiple video cameras, shown, by way of example, as 252 and 254, including provisions 256 for image and data storage utilizing digital tape and other removable media. This remote location may be operated under control from

30   either the main location (as described above), or a local

20

operator, or by specific software designed for automatic control. In the case of software-controlled operations, provisions are included for control to be assumed by the main control center, if necessary. As in the case of the

5 main control computers, each of the remote computers is equipped with intercom facilities as 258 and video cameras as 260.

In the traditional videoconferencing situation, only one camera and monitor are used. Unfortunately, this

10 results in an unnatural scene which provides the users with only a single viewing perspective. The use of a wide-angle camera lens which is needed to include many people seated around a table creates a distorted view, especially for those seated furthest from the camera. Figure 12 shows an

15 overhead view of the typical videoconferencing arrangement, including conference table 300, camera and monitor 302, and conference participants, shown as circles as 304.

Using the PC-based monitoring system, it is possible to create a video conference that presents a much

20 more natural viewing appearance. As shown in Figure 13A, a multiple-camera, multiple-display unit 310 preferably is preferably located directly on the conference table 312. This reduces the camera-perspective-distorting effects just described, because conference members 314 may be seated in

25 a more comfortable and convenient position. The resulting video image is also much more natural. Each controller remote site computer-display section 322 (as described herein below) simultaneously shows all of the members participating in the remote conference, with an individual

30 video window allocated for each participant, under control

21

from the PC-based monitoring system operator. In practice,
the remote site equipment operator will select one of the
display operating modes as described in Figure 15,
depending on the number of subjects (camera views) and the
5   capabilities of the remote site computer equipment.
Optionally, an additional camera 316 fitted with a
wide-angle lens will provide an overall view of the
conference room, in accordance with more traditional
systems.

10   To facilitate the aiming of the individual
cameras for the participants, an arrangement such as that
implemented at airport gates to assist the parking of
airplanes (typically an "I" and an "O" formed of neon light
tubes is utilized for airplane gate parking) optionally may
15   be included. In this case, the two indicators are mounted
so as to overlap only when viewed directly along the
optical axis of the camera lens system. Thus, the camera
position need only be adjusted so as to cause the
indicators to overlap, thereby assuring that the camera
20   correctly is aimed at the subject. A number of microphones
318 are situated around the conference table in locations
suitable for proper audio coverage of the participants'
speech.

          Figure 13B shows a side-view depicting the
25   physical layout of each of the four sides of the multiple-
camera, multiple-display unit 310. The top unit 320 houses
the individual cameras (2 to 8 units) and associated
electronics, optionally including aiming provisions as
described herein above. An LCD display screen 322 shows
30   the various camera images of the conference participants.

Speakers located at positions 324 provide audio from the remote sites.

As shown in Figure 14, the multiple-camera/ display unit shown in Figure 13B preferably is modular in

5   construction including removable side panels, in order to facilitate expansion along either horizontal axis so as to accommodate any size or shape conference table, with each section of the unit serving up to four conference participants. In the preferred embodiment, the entire unit

10   preferably is constructed so as to provide a low profile, by utilizing slanted LCD display panels 330 to create a minimum obstruction for the local conference participants. If a low profile design is not required, the display panels optionally could be larger, and mounted vertically. Until

15   color LCD panels become more cost-effective, the display unit would be constructed with any of the currently available small LCD projector systems. Each conference location may include a designated PC operator, however, the implementation of the network connection facilitates

20   control of the system from a remote location.

It should be noted that the implementation of the PC-based monitoring system is not limited to these examples of security systems or videoconferencing. Many alternative implementations, such as workplace, factory, production

25   line, and process monitoring, would benefit from this system, and these alternative implementations should be considered to be within the scope of the invention.

23